

# INTERMERCATO | Five Finger Grab TG12 - 55SR5



**HARDOX**  
IN MY BODY  
We accept no substitute











### KEY FEATURES

- Mount horizontal for poles or inline
- Heavy duty
- Double guide bars
- Optimized roll in/roll out for logs & bunching
- High pressure cylinder with double piston rod seals
- HARDOX High tensile wear resistant steel (400 HB)
- Reinforced body for rigid mounting - Excavator design
- Optional rotator

WIDE OPENING  
TIGHTER CLOSING

Rotator – upgrade now or later



MODEL SPECIFICATIONS	RIGID MOUNTING 	WEIGHT INCL. HEADBRACKET 	WEIGHT 	GRIP AREA 	PRESSURE 	FLOW 	CLAMPING 	OPEN WIDTH 	CLOSED WIDTH 	CHASSIS WIDTH 
	ton	Kg	Kg	m <sup>2</sup>	Bar	l/min	kN			
TG 12 SR5	1.5-2	75	60	0.12	200	15-30+	8	810	38	273
GRX15-5	2-3.5	110	95	0.14	200	20-50	7	940	63	316
GRX20-5	3.5-5.5	185	170	0.19	250	20-50	11	1234	78	377
GRX25-5	5-8	270	250	0.24	250	20-50	15	1385	85	419
TG 28 SR5	8-12	350	300	0.30	250	60	15	1500	95	512
TG 35 SR5	10-12	450	400	0.38	250	60	18	1890	65	522
TG 42 SR5	12-16	560	480	0.50	250	70	25	1895	100	530
TG 55 SR5	16-24	960	860	0.65	250	90	25	2425	150	635
SUPER HEAVY DUTY										
GX28-50/5	12-18	600	495	0.28	350	60	20	1486	130	632
GX36-50/5	20-30	900	720	0.36	350	60	20	1800	135	658
GX55-50/5	25-32	1935	1735	0.50	350	70	50	2295	145	1010