









INTERMERCATO Rotating Five Finger Grapple



KEY FEATURES

- Made of Hardox
- Extra reinforced body for rigid mounting
- Hardox guide bars from TG16PRO
- Holds load steady at any angle (with optional brake)
- Steel gears & flange for increased durability
- High Pressure Construction
- High torque
- Optimized positioning performance
- Endless 360° rotation
- Optional solenoid if only one set of auxiliaries available
- Custom builds

| MODEL SPECIFICATIONS | RIGID  | WEIGHT  | GRIP AREA  | PRESSURE  | FLOW  | CLAMPING  | OPENING WIDTH  | CLOSING WIDTH  | WORM DRIVE ROTATOR  |
|----------------------|---|--|---|--|--|--|---|---|--|
| | ton | Kg | m ² | Bar | l/min | kN | | | |
| TG12SR5WD7 | 1.5-2 | 115 | 0.12 | 200 | 15-30 | 8 | 810 | 38 | WD7 |
| TG16SR5WD7 | 2-3 | 130 | 0.16 | 200 | 20-40 | 9 | 950 | 60 | WD7 |
| GRX15-5 WD7 | 2-3.5 | 185 | 0.14 | 200 | 20 | 7.2 | 940 | 63 | WD7 |
| GRX20-5 WD9 | 3.5-5.5 | 285 | 0.19 | 200 | 30 | 11.3 | 1234 | 78 | WD9 |
| GRX25-5 WD9 | 5-7.5 | 375 | 0.24 | 250 | 40 | 14.9 | 1385 | 85 | WD9 |
| TG28SR5WD14 | 7-12 | 500 | 0.30 | 250 | 60 | 15 | 1500 | 95 | WD14 |
| TG35SR5WD14/2 | 10-12 | 540 | 0.38 | 250 | 60 | 18 | 1890 | 65 | WD14/2 |
| TG42SR5WD17/2 | 12-16 | 650 | 0.50 | 250 | 70 | 25 | 1895 | 100 | WD17/2 |
| TG55SR5WD21/2 | 16-21 | 1235 | 0.65 | 250 | 90 | 25 | 2425 | 150 | WD21/2 |

HEAVY DUTY OPTION

| | | | | | | | | | |
|------------|-------|------|------|-----|----|----|------|-----|--------|
| GX28WD17/2 | 12-18 | 800 | 0.28 | 350 | 60 | 20 | 1486 | 130 | WD17/2 |
| GX36WD21/2 | 18-24 | 1250 | 0.36 | 350 | 60 | 20 | 1800 | 135 | WD21/2 |
| GX36WD25/2 | 24-30 | 1350 | 0.36 | 350 | 60 | 20 | 1800 | 135 | WD25/2 |
| GX55WD25/2 | 24-32 | 2500 | 0.50 | 350 | 70 | 50 | 2295 | 145 | WD25/2 |

INTERMERCATO

High performance lift and load attachments for Forestry, Transport, Construction and Recycling.

